



Clean It - T

(0-0-0-0)

TL0019

FERTILIZERS

GUARANTEED ANALYSIS

Specific Gravity @ 20°C 1.200 kg/L
pH 1.0 to 2.0



20 L



APPLICATION RATES

Typical Fertigation Application Rates (Overhead Sprinkler/Drip Irrigation):

Dilute in water at a rate of 1:25 ratio for use in cleaning applications: e.g. add 4 litres of Clean It - T to 100 L of water in the fertilizer tank. For a 10,000 Litre fertilizer tank use 20 Litres of Clean It - T to 500 Litres of clean water - apply with a high pressure hose if possible to spray resulting cleaning solution inside the tank. Ensure all surface areas in the tank are rinsed. Or alternatively fill the tank with Clean It - T and water in a 1:25 ratio. Allow 2-3 hours to soak, then wash or rinse twice more with Clean It - T and rinse with clean water. TRIPLE WASHING TANK HIGHLY RECOMMENDED AS A MINIMUM.

GUIDING PRINCIPLES

Before using Clean It - T, seek appropriate agronomic advice via SLTEC's Balanced Agronomy services and dealer agronomist network.

Soil analysis combined with plant tissue (or SAP) analysis are recommended to assist in making an informed decision about which product best meets your crop, soil and general environmental conditions.

Fertilizer can burn and or damage crops and pasture. Because climatic and soil conditions, application methods, irrigation and management practices are beyond the control of Sustainable Liquid Technology Pty Ltd and cannot be foreseen, Sustainable Liquid Technology Pty Ltd accepts no responsibility whatsoever for any commercial damage, loss or other result following the use of this product, whether used in accordance with directions or not, subject to any overriding statutory provision and provided that such liability under those provisions shall be limited to the replacement of the goods as supplied or the rendering again of the services that are provided.

The buyer accepts and uses this product subject to these conditions.

PRODUCT INFORMATION

PRODUCT STORAGE

Keep material in a shaded, cool, dry, well ventilated area, away from direct sunlight between 10 to 30°C. Store product in suitable containers made from material such as stainless steel, high density polyethylene and fibreglass. Fluid fertilizers can be corrosive to material such as brass, copper, zinc or alloys of these metals. Clean equipment after use thoroughly with clean fresh water. Use SLTEC's Fert Tank Cleaner to rinse fertilizer tanks and transfer systems. Clean It - T is recommended for use within 12 months from dispatch date.

WARNING & SAFETY INFORMATION

WARNING: Do not swallow. The spray from this product may act as an irritant. Avoid inhalation and contact with the eyes and skin. Wear rubber gloves and appropriate eye protection when handling the product. See the product SDS for more information, turfandlandscape.com.au

Batch No. or Tank Number & Date:

Dispatch Date:f

PO Box 43 / 2055 Finlay Road
TONGALA VICTORIA 3621

P: 1800 768 224 F: 03 5859 1363

E: enquiries@sltec.com.au

ABN: 63 234 073 378 ACN: 113 670 269

www.sltec.com.au